## Engine Coolant Selection Guide

## **Recochem Coolant Guide**

11100000111	1
All the	ı
ARTHUR ZZ./COOK, ART	l
ALF ADDRESS DE MATERI	ı
~ @ —	ı

duty applications.

www.recochem.com

www.coolantexperts.com



add SCA only as required as

Montréal · Toronto · Edmonton · Vancouver

per OEM instructions.









Properties <b>▼</b>	<b>◎ ◎</b>	STRADIOL II		manual m	O CONTRACTOR OF THE PARTY OF TH	
Product Name/ Product Code	Turbo Power Universal	Turbo Power HD Diesel¹	Turbo Power Global Extended Life <sup>1</sup>	Turbo Power Extended Life <sup>1</sup>	Turbo Power HD Diesel EXL <sup>1</sup>	Turbo Power HD Mixed Fleet ELC
Application	Older model domestic and foreign cars and light duty trucks.	Multi-vehicle fleets including automotive, light duty and heavy duty diesel applications such as on-road truck, off-road and farm applications. Recommended for use where a heavy duty diesel coolant is required, including, but not limited to Caterpillar, Cummins, Detroit Diesel, Ford, GM and Volvo Mack.	All makes and models of domestic and foreign passenger vehicles and light duty trucks.	Newer model domestic and foreign cars and light duty trucks. Can be used in GM cars and trucks requiring Dex-cool®.  Dex-cool® is a registered trademark of General Motors Corporation.	Light and heavy duty diesel applications where an extended service interval is required. Recommended for use in on-road truck, off-road, farm, marine and stationary applications including, but not limited to, Caterpillar, Cummins, Detroit Diesel/MTU, GM Heavy Truck, Freightliner, PACCAR and Volvo Mack.	Complete mixed fleet use; all makes, all models of foreign and domestic automotive, light truck and heavy duty diesel.
Aluminum compatibility	Yes	Yes	Yes	Yes	Yes	Yes
Base fluid	Ethylene glycol	Ethylene glycol	Ethylene glycol	Ethylene glycol	Ethylene glycol	Ethylene glycol
Product pH	10 - 11	10 - 11	7.5 - 8.5	7.5 - 8.6	7.5 - 8.6	8.0 - 9.0
Product colour	Green	Purple	Yellow	Orange	Red	Pale Yellow
Meets performance requirements of	ASTM D3306 ASTM D4985 GM 1825M, 1899M Chrysler M57170 Ford ESE-M97B44-A TMC RP 302B	ASTM D3306 ASTM D4985 ASTM D6210 GM 1825M, 1899M TMC RP 329B Detroit Diesel 7SE298, 93K217	ASTM D3306 Japanese Standard JIS K2234	ASTM D3306 Japanese Standard JIS K2234 Ford WSS-M97B44-D GM 6277 VW TL 774D	ASTM D3306, D4656, D5345, D6210 Japanese Standard JIS K2234 TMC RP329 Detroit Diesel 75E298 CAT EC-1 MTU MTL 5048 CID-A-A-52624 Cummins	ASTM D3306, D4985, D7583, D6210-10 AS.NZ 2108.1:1997 Type A • JIS K2234 GM 1825M, 1899M • BS 6580 DDC 93K217  Recommended for use in: Ford ESE-M97B44A, WSS-M97B44D Kenworth • GM 6277M • PACCARDAF Cummins 14603 • Caterpillar • MACK Freightliner 48-2280 • GM Heavy Truck Chrysler M57170, MS9769 • VW TL774G International Truck & Engine CEMS B-1
CONCENTRATED	16-242, 16-244, 16-245, 26-248, 26-248-1000	16-284, 16-285, 26-289, 26-289-1000	16-104, 26-109	16-374, 26-379	16-734, 26-739, 26-738-1000	16-314, 26-319
50/50 PREMIXED	16-422, 16-424, 26-428, 26-429, 26-429-1000	16-474, 16-475, 26-479, 26-479-1000	16-112, 16-114, 26-119		16-834, 26-839, 26-838-1000	16-324, 16-325, 26-329, 26-329-1000
Recommended change interval	Up to 2 years or 80,000 km		Up to 5 years or 250,000 km	Up to 5 years or 250,000 km	Up to 6 years, 12,000 hours or 960,000 km	Up to 5 years, 250,000 km (automotive) Up to 6 years, 960,000 km (heavy duty diesel)
SCA or coolant extender	SCA compatible for heavy	SCA compatible, monitor and add SCA only as required as		Coolant extender compatible.	SCA extender compatible, use	



Product size availability: 1.89 L, 3.78 L, 9.46 L, 205 L and 1000 L.

only as required by OEM.

## Engine Coolant Selection Guide

## **Recommended Product Applications**

Select Guide		ACTIVITIES OF THE STATE OF THE	HO DIESEL	GLOBAL WILLIAM CONTROL OF THE PARTY OF THE P	ANT PROJECT COM ANY CONTROL OF THE PROPERTY OF	HO DIESEL EXL	HD MIXED TEST ELC AND METERS AND METERS AND AND AND METERS AND AND AND AND METERS AND AND METERS AND AND METERS AND AND METERS AND AND AND METERS AND AND METERS AND AND METERS AND AND METERS AND AND AND METERS AND AND METERS AND AND METERS AND AND METERS AND AND AND METERS AND AND METERS AND AND METERS AND AND METERS AND AND AND METERS AND AND METERS AND AND METERS AND AND METERS AND AND AND METERS AND AND METERS AND AND METERS AND AND AND METERS AND AND METERS AND AND METERS AND AND AND METERS AND AND AND AND	
Vehicle Manufacturer	OEM Antifreeze Colour	Turbo Power Universal	Turbo Power HD Diesel¹	Turbo Power Global Extended life¹	Turbo Power Extended Life¹	Turbo Power HD Diesel EXL <sup>1</sup>	Turbo Power HD Mixed Fleet ELC	
Asian	OEM specific	No	No	Yes	Yes	No	Yes	
Chrysler 2001 and older	Green	Yes	Yes	Yes	No	No	Yes	
Chrysler 2001 to present	Orange	No	No	Yes	No	No	Yes	
European	OEM specific	No	No	Yes	Yes	Yes	Yes	
Ford 2001 and older	Green	Yes	Yes	Yes	Yes	No	Yes	
Ford 2002 trucks/ 2003 cars	Gold	No	No	Yes	Yes	No	Yes	
Heavy Duty Diesel	OEM specific	Yes	Yes	No	Yes	Yes	Yes	
General Motors 1994 and older	Green	Yes	Yes	Yes	Yes	No	Yes	
General Motors 1995 to present	Orange	No	No	Yes	Yes	No	Yes	
Saturn	Orange	No	No	Yes	Yes	No	Yes	



www.recochem.com

www.coolantexperts.com

Product size availability: 1.89 L, 3.78 L, 9.46 L, 205 L and 1000 L.