



CHRYSLER/FORD VEHICLE EXTENDED LIFE ANTIFREEZE/COOLANT PREMIXED 50/50

RECOMMENDED FOR:

Chrysler®, Dodge®, Jeep®, Ford®, Lincoln®, Mercury® vehicles

FORMULATION FEATURES:

- Hybrid engine technology for extended rust and corrosion protection
- For gasoline & light duty diesel vehicles
- Engineered for high-heat engines
- Maximum aluminum protection
- Low silicate; phosphate and amine free

APPLICATION:

North American gasoline and light duty diesel vehicles. All Chrysler (1995-2011) and Ford (1995-2009) models.

PERFORMANCE RATED AT

5 YEARS OR
250000 KM *

Item#	Units/Case	UPC#	SCC14
36-834GSTPCF	3.78 L / 4	0-59934-90643-8	400-59934-90643-6



STP_CHRYCAMEN_0615



Recochem Inc.
Your Partner in Formulating Solutions

Montréal • Toronto • Edmonton • Vancouver • www.recochem.com • www.coolantexperts.com



CHRYSLER/FORD VEHICLE EXTENDED LIFE ANTIFREEZE/COOLANT PREMIXED 50/50

STP® Chrysler/Ford Vehicle Extended Life 50-50 Premixed Antifreeze/Coolant meets or exceeds performance requirements of ASTM D3306, SAE J1034, Chrysler MS7170, MS9769, US Fed A-A-870-A and is recommended for use and fully compatible with product meeting Ford WSS-M97B51-A1.

This robust, aluminum compatible hybrid engine coolant is low in silicate and is phosphate and amine-free. It provides excellent high temperature aluminum performance in older model Chrysler (1995-2011) and Ford (1995-2009) gasoline and light duty diesel powered vehicles.

*When added as an initial fill and properly maintained in accordance with engine manufacturer's maintenance recommendation, STP® Chrysler/Ford Vehicle Extended Life Antifreeze/Coolant provides up to 250,000 km or 5 years of service life protection in automotive and light duty truck applications.

OEM specification/performance level:

ASTM D3306; SAE J1034; Chrysler MS7170, MS9769; US Fed A-A-870-A
Compatible with Ford WSS-M97B51-A1

Typical Product Properties

Characteristic	Performance	Test Method
pH ^a	7.5 - 8.6	ASTM D1287
Specific gravity ^b	1.125 - 1.140	ASTM D1122
Freeze point (°C/°F)	-37/ -34	ASTM D1177
Foam volume (ml)	150 max.	ASTM D1881
Foam break time (second)	5 max.	ASTM D1881
Reserve Alkalinity (ml)	6.0 min.	ASTM D3634
Chloride (ppm)	25 max.	
Colour	Gold	
Glycol Content (wgt.%)	94 min.	
Inhibitors and Water Content (wgt.%)	6.0 max.	
Silicon (ppm)	250 max.	ASTM D6130

^a 50% volume aqueous solution

^b Measured at 15.6°C/60°F

Item#	Units/Case	UPC#	SCC14
36-834GSTPCF	3.78 L / 4	0-59934-90643-8	400-59934-90643-6



NOTICE: This product is shipped in compliance with applicable laws and regulations regarding classification, packaging, shipping and handling. The performance and physical property data described for this product are typical results not sale specifications, except where maximum or minimum is indicated. Refer to Material Safety Data Sheets for further information.

Because use conditions and applicable laws may differ from one location to another and may change with time, the customer is responsible for determining whether product and the information in this document are appropriate for their use and for ensuring that their workplace and disposal practices are in compliance with applicable laws and other governmental enactments. The Antifreeze/Coolant's warranty is limited to the claims of product meeting stated performance specifications. It is the responsibility of the end-user to determine product suitability as recommended in the owner's manual and to follow engine manufacturer's instructions.

The STP trademark and logo are registered trademarks of The Armor All/STP Products Company and are used under license by Rechem Inc. All rights reserved.



Recochem Inc.
Your Partner in Formulating Solutions

Montréal • Toronto • Edmonton • Vancouver • www.recochem.com • www.coolantexperts.com