



GLOBAL EXTENDED LIFE ANTIFREEZE/COOLANT



- Recommended for use in **ALL MAKES AND MODELS** of foreign and domestic passenger vehicles and light duty trucks
- **GUARANTEED UP TO: 5 years or 150,000 miles protection***
- Add as a top-up to any color antifreeze
- Protects all coolant system metals, including aluminum
- Available as a **CONCENTRATE** or **50/50 PRE-DILUTED**

ITEM#	FORMULATION	SIZE	CASE PACK	UPC	SCC
36-104STPEXP	Concentrate	1 Gallon	4	059934901204	40059934901202
36-104STPXPR (\$2 rebate)	Concentrate	1 Gallon	4	059934903505	40059934903503
36-114STPEXP	Pre-diluted	1 Gallon	4	059934901297	40059934901295
36-114STPXPR (\$2 rebate)	Pre-diluted	1 Gallon	4	059934902416	40059934902414

STP® Global Extended Life Antifreeze/Coolant is recommended for use in ALL MAKES AND MODELS of foreign and domestic passenger vehicles and light duty trucks. It contains a proprietary formulation of premium corrosion inhibitors that provide extended protection against rust, corrosion and pitting caused by cavitation for all coolant system metals. It also provides excellent protection against temperature extremes, preventing freeze-up and boil-over when used in accordance with OEM and product manufacturer's guidelines regarding product dilution. This product can be mixed with any color engine coolant. *When added to a coolant system after a complete drain, flush and fill, this product provides up to 5 years or 150,000 miles of protection.

Coolant concentrate must be diluted with water prior to use. **STP® Global Extended Life Antifreeze/Coolant** should not be used in concentrated form. A 50% dilution is generally recommended for the best balance of protection against freezing, corrosion and summer boil-over. For increased freeze protection in extremely cold areas, a 60% volume concentration can be used. Concentrations of greater than 70% by volume are not recommended. High quality soft, de-ionized or distilled water should always be used to dilute coolant concentrate. For added value and convenience, this product is available in a ready to use format, pre-diluted to 50% volume using de-ionized water.

ECONOMY: Save your customers' money by reducing the number of times they need to change their coolant. The superior performance and stability of our premium extended life corrosion inhibitors allows them to go on working well beyond the lifetime of traditional products.

EXTENDED PERFORMANCE: Our proprietary extended life engine coolant technology affords lasting corrosion protection and protects against pitting caused by cavitation to the ferrous and non-ferrous metals currently found in traditional and modern engine/ engine coolant system construction. When added to a coolant system after a complete drain, flush and fill, this product provides up to 5 years or 150,000 miles of protection.

Chemical Name: Ethylene Glycol-based Engine Coolant

Typical Product Properties:

Characteristic	Performance	Test Method
pH (50% by vol.)	7.5 – 8.5	ASTM D1287
Specific gravity (15.6°C/60°F)	1.120 – 1.140	ASTM D1122
Freeze point (50% by vol.)	-37°C/ -34°F	ASTM D1177
Foam volume (ml)	150 max.	ASTM D1881
Foam break time (second)	5 max.	ASTM D1881
Reserve Alkalinity (ml)	3.0 min.	ASTM D1121
Chloride (ppm)	25 max.	ASTM D3634
Color	Pale Yellow	
Glycol Content (wgt.%)	93 min.	
Inhibitors and Water Content (wgt.%)	7 max.	

Meets the following specifications:
ASTM D3306, JIS K2234



NOTICE: This product is shipped in compliance with applicable laws and regulations regarding classification, packaging, shipping and handling. The performance and physical property data described for this product are typical results not sale specifications, except where maximum or minimum is indicated. Refer to Material Safety Data Sheets for further information.

Because use conditions and applicable laws may differ from one location to another and may change with time, the customer is responsible for determining whether product and the information in this document are appropriate for their use and for ensuring that their workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Recochem's warranty is limited to the claims of product meeting stated performance specifications. It is the responsibility of the end-user to determine product suitability as recommended in the owner's manual and to follow engine manufacturer's instructions.

The STP trademark and logo are registered trademarks of The Armor All/STP Products Company and are used under license by Recochem Inc. All rights reserved.