



# TURBO POWER<sup>®</sup>

## TURBO POWER 50/50 PRE-DILUTED ANTIFREEZE COOLANT

- Protects against winter freezing and summer boil over
- Prevents pitting caused by cavitation and corrosion of brass, copper, solder, steel, cast iron and aluminum
- Low silicate
- Recommended for older model domestic and foreign cars and light duty trucks
- Aluminum compatible
- Pre-diluted – DO NOT ADD WATER



**Recochem Inc.**  
Your Partner in Formulating Solutions

[www.recochem.com](http://www.recochem.com)



# TURBO POWER<sup>®</sup>

## TURBO POWER 50/50 PRE-DILUTED ANTIFREEZE COOLANT

**PRODUCT DESCRIPTION:** Turbo Power All Season 50/50 Pre-diluted Antifreeze/Coolant is a superior quality ethylene glycol based low silicate engine coolant. This product protects coolant system metals, including heat-rejecting aluminum, against pitting caused by cavitation and corrosion. It provides exceptional cooling in summer and excellent protection against freezing in the winter. It provides optimum protection against radiator freeze-up down to -37°C and boil-over to 129°C (with a 100 kilopascal {15 psi} radiator cap in good condition). It is recommended for use in older model domestic and foreign cars and light duty trucks. This product meets the performance requirements of ASTM D-3306, D-4985, GM 1825M/1899M, DaimlerChrysler MS7170, Ford ESE-M97B44-A and TMC RP 302B.

**APPLICATIONS:** This product is recommended for use in older model domestic and foreign cars and light duty trucks.

### TURBO POWER 50/50 PRE-DILUTED ANTIFREEZE COOLANT

Chemical Name: Ethylene Glycol Based Engine Coolant  
Description: Green Liquid

### REQUIREMENTS:

Test	Performance	Test Method
pH (as is)	10 – 11	ASTM D-1287
Specific Gravity (15.6°C/60°F)	1.075 – 1.085	ASTM D-1122
Freeze Point (as is)	-37°C/-34°F	ASTM D-1177
Foam Volume (mL)	50 max.	ASTM D-1881
Foam Break Time (sec.)	5 max.	ASTM D-1881
Color	Green	
Total Glycols (wt.%)	47 min.	
Inhibitors and Water (wt.%)	53 max.	
Chloride (ppm)	25 max.	ASTM D-3634



Read precautionary and material safety sheets. This product is shipped in compliance with applicable laws and regulations regarding classification, packaging, shipping and handling.

Available in 1 qt, 1 gal, 2.5 gal and 55 gal sizes.

The performance and physical property data described for this product are typical results, not sale specifications, except where maximum or minimum is indicated.

**NOTICE:** Because use conditions and applicable laws may differ from one location to another and may change with time, the customer is responsible for determining whether product and the information in this document are appropriate for their use and for ensuring that their workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Recochem's warranty is limited to the claims of product meeting stated performance specifications. It is the responsibility of the end-user to determine product suitability as recommended in the owner's manual and to follow engine manufacturer's instructions.



**Recochem Inc.**  
Your Partner in Formulating Solutions

Montréal • Toronto • Edmonton • Vancouver

[www.recochem.com](http://www.recochem.com)

10-326-06