



OEM[®]

ORIGINAL EQUIPMENT MANUFACTURER

GLOBAL EXTENDED LIFE ANTIFREEZE/COOLANT

- NEW FORMULA!
- Fastest growing segment of engine coolant aftermarket
- Recommended for use in ALL MAKES AND MODELS of foreign and domestic passenger vehicles and light duty trucks
- Add as top-up to any color antifreeze
- Protects all coolant system metals, including aluminum
- Guarantee: Up to 5 years or 150,000 miles protection whichever comes first when added as initial fill or when added to a coolant system after a complete drain, flush and fill
- Extended coolant system performance
- Available as a 50/50 premix



Recochem Inc.
Your Partner in Formulating Solutions

www.recochem.com



GLOBAL EXTENDED LIFE ANTIFREEZE/ COOLANT

PRODUCT DESCRIPTION: Global Extended Life Antifreeze/Coolant is recommended for use in ALL MAKES AND MODELS of foreign and domestic passenger vehicles and light duty trucks. It contains a proprietary formulation of premium corrosion inhibitors that provide extended protection against rust, corrosion and pitting caused by cavitation for all coolant system metals. It also provides excellent protection against temperature extremes, preventing freeze-up and boil over when used in accordance with OEM and product manufacturer's guidelines regarding product dilution. This product can be mixed with any color engine coolant. When added to a coolant system after a complete drain, flush and fill, this product provides up to 5 years or 150,000 miles of protection. Global Extended Life Antifreeze/Coolant meets the performance requirements of ASTM D-3306 and Japanese Industry Standard K-2234.

Never use 100% coolant in concentrated form. A 50% dilution (i.e. when mixed with an equal volume of high quality soft, de-ionized or distilled water) is generally recommended for the best balance of protection against freezing, corrosion and summer boil over. For increased freeze protection in extremely cold areas, a 60% volume concentration can be used. Concentrations of greater than 70% by volume are not recommended.

ECONOMY: Save your customers' money by reducing the number of times they need to change their coolant. The superior performance and stability of Recochem's premium extended life corrosion inhibitors allows them to go on working well beyond the lifetime of traditional products.

EASE OF USE: This product is recommended for use in ALL MAKES AND MODELS of foreign and domestic passenger vehicles and light duty trucks. When pre-diluted with soft or de-ionized water, it can be added to any color antifreeze/coolant.

EXTENDED PERFORMANCE: Recochem's proprietary extended life engine coolant technology affords lasting corrosion protection and protects against pitting caused by cavitation to the ferrous and non-ferrous metals currently found in traditional and modern engine/engine coolant system construction. When added to a coolant system after a complete drain, flush and fill, this product provides up to 5 years or 150,000 miles of protection.

GLOBAL EXTENDED LIFE ANTIFREEZE/COOLANT

Chemical Name: Ethylene Glycol Based Engine Coolant
Description: Luminescent Yellow Liquid

REQUIREMENTS:

Test	Performance	Test Method
pH (50% by vol.)	7.8 - 8.5	ASTM D-1287
Specific Gravity (15.6°C/60°F)	1.120-1.140	ASTM D-1122
Freeze Point (50% by vol.)	-37°C/-34°F max.	ASTM D-1177
Foam Volume (mL)	50 max.	ASTM D-1881
Foam Break Time (sec.)	5 max.	ASTM D-1881
Flash Point	116°C/240°F	ASTM D-92
Color	Yellow	
Total Glycols (wt.%)	93 min.	
Inhibitors and Water (wt.%)	7.0 max.	
Chloride (ppm)	25 max.	ASTM D-3634

Read precautionary and material safety sheets. This product is shipped in compliance with applicable laws and regulations regarding classification, packaging, shipping and handling.

Available in 1 qt, 1 gal, 2.5 gal and 55 gal sizes.



The performance and physical property data described for this product are typical results, not sale specifications, except where maximum or minimum is indicated.

NOTICE: Because use conditions and applicable laws may differ from one location to another and may change with time, customers are responsible for determining whether product and the information in this document are appropriate for their use and for ensuring that their workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Recochem's warranty is limited to the claims of product meeting stated performance specifications. It is the responsibility of the end-user to determine product suitability as recommended in the owner's manual and to follow engine manufacturer's instructions.



Recochem Inc.
Your Partner in Formulating Solutions

Montréal • Toronto • Edmonton • Vancouver

www.recochem.com