

USING Heirloom® STRIPPERS

To remove paint from porous surfaces, such as brick and concrete, instead of using a scraper, use a stiff scrubbing brush to get softened paint out of crevices.

Wait 24 hours and then apply a new finish. No other treatment is necessary.

Heirloom® strippers are effective and safe for use on antiques or fine wood, masonry and metal.

It will not harm veneer or raise the grain on wood, however do not expose the product to linoleum, asphalt, vinyl or rubber tiles. Avoid contact with rugs, floors, fabrics or plastics, including fiberglass.



WARNING:

Never use in combination with a heated scraper/gun or open flame to remove old finish. Open carefully, pressure may build up in can. DO NOT use on linoleum, asphalt, plastic, vinyl or rubber surfaces. Avoid contact with rugs, textiles, fabrics or plastics, including fiberglass. To prevent damage to floor surfaces, cover work area. Do not apply to large areas or floors as flammability and health risks will increase dramatically; ensure proper ventilation while using. Test on an inconspicuous area first. During use, if the rubber gloves become hot, change to a new pair of gloves.

DISPOSAL/STORAGE:

Save the remainder for future projects in original container tightly sealed. Do not transfer into unlabeled containers. Dispose of any leftover product safely according to hazard waste requirements. Place used rags and scrapings in the garbage. Keep away from open flames, such as a pilot light and heaters, and any object that sparks, such as an electric motor. Store in a cool area and protect from freezing. The product will keep for at least two years when stored properly.



PROUDLY MADE IN QUEBEC, CANADA

Proudly produced in Canada, Heirloom® products offer the assurance you are buying quality formulas.

THE MC FREE LINE-UP

Heirloom® MAX HEAVY DUTY STRIPPER CONTRACTOR STRENGTH

- Non-drip for vertical surfaces
- Strips Glues & Adhesives, ALL Finishes & Paints from Wood, Metal, Plaster, Glass and Masonry
- Fast Acting; Removes 5 or more layers
- Suitable for use on latex, polyurethane or oil/alkyd coatings



Heirloom® PLUS PAINT STRIPPER RESTORATION FRIENDLY

- Penetrates intricate surfaces
- Strips Paint, Varnish & Stains from Wood, Metal, Glass, Plaster & Masonry
- Fast Acting; Removes 5 layers or more
- Suitable for use on latex, polyurethane or oil/alkyd coatings



Heirloom® PURE PAINT STRIPPER INDOOR RESTORATION

- Water-rinseable
- Low odour; VOC compliant
- GENTLY strips away Paint & Varnish from Wood, Metal, Glass & Masonry



Watch our How-To Video on YouTube



www.heirloompaintstripper.com



FAST RESTORE YOUR PROJECTS WITH

Heirloom® STRIPPERS

METHYLENE CHLORIDE FREE

- FAST-ACTING
- SMOOTH FINISH
- MULTILAYER REMOVER
- WATER-RINSEABLE

WORKS IN 15 MIN.



RESTORE, REVEAL & REPURPOSE!

HEIRLOOM_EN_0419

Heirloom[®] STRIPPERS

The 'DIY' SOLUTION

There are different types of paint strippers to choose from, and it is important to find the right one for your refinishing project. Heirloom[®] Strippers outperform competitor products and are the next generation breakthrough Methylene Chloride free formulas, that are equally effective as prior technologies!

Heirloom[®] semi-gel and thick-gel formulas work quickly to effectively remove layers of paint, varnish and coating from all woods, metal, plaster, glass and masonry.

Heirloom[®] strippers eliminate the need for harsh sanding and will not raise the wood grain for a smooth finish.

RECOMMENDED TOOLS & MATERIALS:

Disposable paint brush	Heirloom [®] MC FREE Stripper
Clean cloth	Lint-free cloth
Chemical-resistant gloves	Solvable Paint Thinner
Eye Protection	Newspaper or drop-cloth
Metal scraping tool	Mask or organic vapour respirator



4 STEPS TO A FAST RESTORATION



STEP 1

Read the product label before using. **Shake well** before use. **Apply liberally** to surface with a paint brush. Work on a small area at a time and let stand for 15 minutes or until finish has softened.



STEP 2

Remove loosened finish by scraping in direction of surface grain with a metal scraping tool. Repeat applications may be needed for stubborn finishes.



STEP 3

Wipe surface with **Stripper** to eliminate any loosened residual coating.



STEP 4

To ensure surface is clean, use another cloth dampened with Paint Thinner. When surface is completely dry, apply a new finish.



BEFORE



AFTER