

UNIVERSAL ANTIFREEZE+COOLANT

NEW LOOK

LOW SILICATE

NOW



AN ETHYLENE GLYCOL BASED ENGINE COOLANT WITH A LOW SILICATE CORROSION INHIBITOR PACKAGE. THIS PRODUCT HELPS PROTECT COOLANT SYSTEM METALS, INCLUDING HEAT-REJECTING ALUMINUM, AGAINST PITTING CAUSED BY CAVITATION AND CORROSION. IT PROVIDES COOLING IN SUMMER AND PROTECTION AGAINST FREEZING IN THE WINTER. IT IS RECOMMENDED FOR USE IN OLDER* MODEL DOMESTIC AND FOREIGN CARS AND LIGHT-DUTY TRUCKS AND WILL PROVIDE UP TO 80,000 KM OR 2 YEARS SERVICE LIFE†.

ETHYLENE GLYCOL
BASED IAT FORMULA

EXCELLENT PROTECTION AGAINST TEMPERATURE
EXTREMES: FROM -64°C UP TO 136°C
(WITH A 70/30 DILUTION RATE)‡

MEETS THE PERFORMANCE
REQUIREMENTS OF: ASTM
D3306 & D4985



FOR USAGE IN
ENGINE RADIATORS



PERFECT FOR HARSH
WINTER CONDITIONS

TYPICAL PRODUCT PROPERTIES FOR 50/50 PRE-DILUTED ANTIFREEZE+COOLANT

CHARACTERISTICS	PERFORMANCE	TEST METHOD
pH	10 - 11	ASTM D1287
SPECIFIC GRAVITY (15.6°C)	1.070 - 1.090	ASTM D1122
FREEZING POINT (50% BY VOLUME)	-37°C	ASTM D1177
FOAM VOLUME (ml)	150 MAX.	ASTM D1881
FOAM BREAK TIME (SECONDS)	5 MAX.	ASTM D1881
RESERVE ALKALINITY (ml)	3.4 MIN.	ASTM D1121
CHLORIDE (ppm)	25 MAX.	ASTM D3634
SILICON (ppm)	125 MAX.	ASTM D6130
COLOUR	GREEN	



TURBO POWER™ ANTIFREEZE+COOLANT IS AVAILABLE IN 1.89 L, 3.78 L, 9.46 L, DRUMS & TOTES

FOR MORE INFORMATION ON 1.89 L & 9.46 L CONTACT YOUR SALES REPRESENTATIVE

PRODUCT SPECIFICATIONS

BOTTLE				
ITEM #	FORMULATION	UNIT/CASE PACK	UPC	SCC14
16-424	PREDILUTED 50/50	4 X 3.78 L	056438164241	60056438153551
16-244	CONCENTRATE	4 X 3.78 L	056438162445	60056438153551
DRUM / TOTE				
ITEM #	FORMULATION	UNIT/CASE PACK	UPC	SCC14
26-429US	PREDILUTED 50/50	1 X 208 L	056438909965	-
26-249	CONCENTRATE	1 X 208 L	056438909941	-
26-429-275	PREDILUTED 50/50	1 X 1041 L	056438909156	-
26-249-275	CONCENTRATE	1 X 1041 L	056438909118	-

*OLDER VEHICLES ARE MANUFACTURED IN OR BEFORE THE YEAR 2004.
‡THIS TEMPERATURE PROTECTION RANGE CAN BE ACHIEVED WHEN DILUTING THE ANTIFREEZE+COOLANT CONCENTRATE AT A 70/30 RATE WITH DEIONIZED WATER.

†WHEN ADDED TO A COOLANT SYSTEM AFTER A COMPLETE DRAIN, FLUSH AND FILL,
THIS PRODUCT PROVIDES UP TO 80,000 KM OR 2 YEARS OF PROTECTION, WHICHEVER OCCURS FIRST.