

GLOBAL EXTENDED LIFE ANTIFREEZE/COOLANT



Application:

ALL MAKES AND MODELS of foreign and domestic passenger vehicles and light duty trucks.

- Add as a top-up to any color antifreeze
- Protects all cooling system metals, including aluminum
- **PERFORMANCE RATED AT:** Up to **5 years** or **150,000 miles** service life protection*

Typical Product Properties for 50/50 Pre-diluted:

Characteristic	Performance	Test method
pH	7.5 – 8.5	ASTM D1287
Specific gravity (15.6°C/60°F)	1.065 – 1.085	ASTM D1122
Freeze point (50% by volume)	-37°C/ -34°F	ASTM D1177
Foam volume (ml)	150 max.	ASTM D1881
Foam break time (second)	5 max.	ASTM D1881
Reserve Alkalinity (ml)	1.8 min.	ASTM D1121
Chloride (ppm)	25 max.	ASTM D3634
Color	Pale Yellow	
Glycol Content (wgt.%)	46 min.	
Inhibitors and Water Content (wgt.%)	54 max.	

Meets the performance requirements of:

ASTM D3306

Japanese standard JIS K2234

TURBO POWER Global Extended Life Antifreeze/Coolant is recommended for use in **ALL MAKES AND MODELS** of foreign and domestic passenger vehicles and light duty trucks. It contains a proprietary formulation of premium corrosion inhibitors that provide extended protection against rust, corrosion and pitting caused by cavitation for all coolant system metals. It also provides excellent protection against temperature extremes, preventing freeze-up and boil-over when used in accordance with OEM and product manufacturer's guidelines regarding product dilution. This product does not impart any color change if mixed with another engine coolant. The superior performance and stability of its premium extended life corrosion inhibitors allows them to go on working well beyond the lifetime of traditional products.

*When added to a coolant system after a complete drain, flush and fill, this product provides up to 5 years or 150,000 miles of protection.

Item #	Formulation	Container Size	Case Pack	UPC	SCC
86-104OEM	Concentrate	1 Gal. (3.78 L)	4	0-56438-86104-1	400-56438-86104-9
86-114OEM	50-50 Pre-diluted	1 Gal. (3.78 L)	4	0-56438-86114-0	400-56438-86114-8
86-109OEM	Concentrate	55 Gal. (205 L)	NA	NA	NA
86-119OEM	50-50 Pre-diluted	55 Gal. (205 L)	NA	NA	NA
86-109-1000	Concentrate	264 Gal. (1,000 L)	NA	NA	NA



Recochem Inc.
Your Partner in Formulating Solutions

www.recochem.com • www.coolantexperts.com