



# AUTOMOTIVE COOLANT TECHNOLOGIES

## ENGINE COOLANT SELECTOR GUIDE



PRODUCT NAME		Turbo Power Global Extended Life <sup>1</sup>	Turbo Power Extended Life <sup>1</sup>	Turbo Power Universal
APPLICATION		All makes and models of domestic and foreign passenger vehicles and light duty trucks.	Newer model domestic and foreign cars and light duty trucks. Can be used in GM cars and trucks requiring Dex-cool®.	Older model domestic and foreign cars and light duty trucks.
FORMULATIONS		OAT based; Silicate, borate, phosphate, nitrite and amine free	OAT based; Silicate, borate, phosphate, nitrite and amine free	Low silicate; Aluminum compatible
LIQUID COLOUR		Yellow	Orange	Green
CONCENTRATE		16-104, 26-109	16-374, 26-379	16-242, 16-244, 16-245, 26-248, 26-248-1000
50/50 PREMIX		16-112, 16-114, 26-119		16-422, 16-424, 26-428, 26-429, 26-429-1000
RECOMMENDED CHANGE INTERVAL		Up to 5 years or 250,000 km	Up to 5 years or 250,000 km	Up to 2 years or 80,000 km
VEHICLE MANUFACTURER	OEM COLOUR	RECOMMENDED PRODUCT APPLICATIONS		
ASIAN	OEM specific	●	●	
CHRYSLER 2001 & OLDER	Green	●		●
CHRYSLER 2001-PRESENT	Orange	●		
EUROPEAN	OEM specific	●	●	
FORD 2001 & OLDER	Green	●	●	●
FORD 2002 TRUCKS / 2003 CARS	Gold	●	●	
HEAVY DUTY DIESEL	OEM specific		●	●
GM 1994 & OLDER	Green	●	●	●
GM 1994-PRESENT	Orange	●	●	
SATURN	Orange	●	●	

**Product size availability: 1.89 L, 3.78 L, 9.46 L, 208 L and 1000 L.**

Information above includes recommendations for aftermarket use. Refer to owner's manual for suggested manufacturer's coolants and warrantee issues.

1. A propylene glycol-based version of this product is available, based on demand.

RECOCHEM.COM • COOLANTEXPerts.COM

