



Recochem Inc.  
Your Partner in Formulating Solutions

## OIL PRODUCTS

# Pale Boiled Linseed Oil

## DESCRIPTION

Treated linseed oil, commonly called "**Boiled Linseed Oil**" is obtained by pressing seeds of the flax plant. It is primarily used as a timber preserver as it offers increased water resistance.

## FEATURES

Dries faster than Raw Linseed Oil.

Has added drying agents to speed up drying time.

When applied to a porous surface it fills the pores and as it is exposed to air it gels to form a protective film.

When added to oil-based paints it helps brushing and aids timber protection.

Increases water resistance.

Commonly used as a sealer and protective coating for concrete paths and floors, flagstones or interlocking stones as well as a timber stainer.

## PACKAGING

**Pale Boiled Linseed Oil** is available in drums and 20 litre containers.

## SAFETY

Please consult the MSDS on **Pale Boiled Linseed Oil** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

## Typical Characteristics

Appearance .....	golden-brown viscous fluid
Specific Gravity.....	0.92
Flash Point.....	150°C
Auto Ignition Point.....	350°C



**MSDS** available

**QUEENSLAND**  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

**NEW SOUTH WALES**  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

**VICTORIA**  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

**SOUTH AUSTRALIA**  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

**WESTERN AUSTRALIA**  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033

© Copyright Recochem Inc. All rights reserved. All content remains the property of Recochem Inc. All other trademarks mentioned are trademarks or registered trademarks of their respective owners. All text, images, graphics and PDF files are subject to the copyrights and intellectual property rights of Recochem Inc. Separate to the purpose of review and private use, this information cannot be used without written permission from Recochem. Information contained herein is for general information only and should not be used as an infallible to a product's specification and or performance.