

OIL PRODUCTS

Raw Linseed Oil

DESCRIPTION

An untreated linseed oil obtained by pressing seeds of the flax plant. **Raw Linseed Oil** is crude oil and has a longer drying time than Boiled Linseed Oil.

FEATURES

When applied to a porous surface it fills the pores and as it is exposed to air it gels to form a protective film.

Protective finish for most timbers (creates a finish that is generally impervious to water, heat, scratches and most stains).

Raw Linseed is suitable for outdoor timber.

Increases water resistance.

Furniture oil to maintain and protect wood finishes - provides a light stain on pale woods.

Part of the process to create a "French Finish" for timber.

PACKAGING

Raw Linseed Oil is available in drums and 20 litre containers.

SAFETY

Please consult the MSDS on **Raw Linseed Oil** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

| | |
|--------------------------|-------------------------------|
| Appearance | golden-brown viscous fluid |
| Specific Gravity..... | 0.92 |
| Flash Point..... | 150°C |
| Auto Ignition Point..... | 350°C |



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033

© Copyright Recochem Inc. All rights reserved. All content remains the property of Recochem Inc. All other trademarks mentioned are trademarks or registered trademarks of their respective owners. All text, images, graphics and PDF files are subject to the copyrights and intellectual property rights of Recochem Inc. Separate to the purpose of review and private use, this information cannot be used without written permission from Recochem. Information contained herein is for general information only and should not be used as an infallible to a product's specification and or performance.