



# **SAFETY DATA SHEET**

SECTION 1 IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Identifier DIGGERS ENAMEL THINNERS

Other Names Mixed aromatic, paraffinic and naphthenic hydrocarbon

Manufacturer's Product Code 17032

Recommended Use Solvent

**Details of Supplier/Manufacturer** 

Company:	Recochem Inc. ABN: 69 010 485 999	
Address:	1809 Lytton Road, Lytton, Queensland 4178	
Phone:	(07) 3308 5200 Fax: (07) 3308 5201	
Website:	www.recochem.com.au	

#### **Details of Distributor**

Company:	Owens Logistics		
Address:	3-5 Kahu Street,	Otahuhu, Auckland	
Phone:	(09) 270 1310	Fax: (09) 270 1311	

**Emergency Telephone Number** 

	Poisons Information:	0800 764 766
--	-------------------------	--------------

### SECTION 2 HAZARDS IDENTIFICATION

Hazardous chemical	according to classification by Safe Work Australia
Dangerous goods	according to the Australian Code for the Transport of Dangerous Goods by Road and Rail

GHS Classification	Pictogram	Hazard statement
Flammable Liquids, Category 2	FLAME	H225 Highly flammable liquid and vapour
Aspiration Hazard, Category 1		H304 May be fatal if swallowed and enters airways
Reproductive Toxicity, Category 1A		H360 May damage fertility or the unborn child

Page 1 of 7 ISSUE DATE: 22/12/2021

Specific Target Organ Toxicity (Repeated exposure), Category 1		H372 Cause damage to organs through prolonged or repeated exposure
Carcinogenicity, Category 1A		H350 May cause cancer
Germ Cell Mutagenicity, Category 1B	HEALTH HAZARD	H340 May cause genetic defects
Serious Eye Damage/Eye Irritation, Category 2A		H319 Causes serious eye irritation
Skin Corrosion/Irritation, Category 2	EXCLAMATION MARK	H315 Causes skin irritation

## **Precautionary statements:**

Precautionary statements:		
GENERAL		
P101	If medical advice is needed, have product container or label at hand	
P102	Keep out of reach of children	
P103	Read label before use	
PREVENTATIVE		
P201	Obtain special instructions before use	
P202	Do not handle until all safety precautions have been read and understood	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P233	Keep container tightly closed	
P240	Ground and bond container and receiving equipment	
P241	Use explosion-proof electrical/ventilation/lighting equipment	
P242	Use non-sparking tools	
P243	Take action to prevent static discharge	
P260	Do not breathe mist/vapours/spray	
P264	Wash thoroughly after handling	
P270	Do not eat, drink or smoke when using this product	
P280	Wear protective gloves/eye protection/face protection	
RESPONSE		
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician	
P302 + P352	IF ON SKIN: Wash with plenty of soap and water	
P303 + P361 + P353	IF ON SKIN (or hair): Take off contaminated clothing and wash before reuse.  Rinse skin with water/shower	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing	
P308 + P313	IF exposed or concerned: Get medical advice/attention	
P314	Get medical advice/attention if you feel unwell	
P331	Do NOT induce vomiting	
P332 + P313	If skin irritation occurs: Get medical advice/attention	
P337 + P313	If eye irritation persists: Get medical advice/attention	
P362 + P364	Take off contaminated clothing and wash before reuse	
P370 + P378	In case of fire: Use foam/water spray/fog to extinguish	
STORAGE		
P403 + P235	Store in a well-ventilated place. Keep cool	
P405	Store locked up	
DISPOSAL		
P501	Dispose of contents/container in accordance with local regulations	

Page 2 of 7 ISSUE: 5 ISSUE DATE: 22/12/2021

### SECTION 3 COMPOSITION AND INFORMATION ON INGREDIENTS

#### **Ingredients Names and Proportions**

Chemical Entity	CAS Number	Proportion (%)
Toluene	108-88-3	40 – 60
Solvent naphtha (petroleum), light aliphatic	64742-89-8	40 – 60
n-Hexane	110-54-3	< 5
Note – product contains < 0.1% benzene		

#### SECTION 4 FIRST AID MEASURES

### Description of necessary first aid measures

Inhalation:	Remove victim from exposure if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing.
Skin Contact:  If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available.	
Eye Contact:  If in eyes, hold eyes open, flood with water for at least 15 minutes. If symptoms persist transport to nearest medical facility for additional treating the symptoms persist transport to nearest medical facility.	
Ingestion:	If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

#### Symptoms caused by exposure

ptome dauged by expectate		
Breathing of high vapour concentrations may cause central nervous sy depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.		
Skin:	May include burning sensation and/or a dried/cracked appearance.	
Eye:	May include burning sensation, redness, swelling and/or blurred vision.	
Ingestion:	May include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath and/or fever.	

### Medical attention and special treatment

Treat symptomatically.

#### SECTION 5 FIRE FIGHTING MEASURES

### Suitable extinguishing equipment

Foam, water spray or fog, dry chemical powder or carbon dioxide. Do not use water in a jet.

### Specific hazards arising from the chemical

Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. Vapour is heavier than air, can spread along ground and distant ignition is possible.

#### Special protective equipment and precautions for fire fighters

Wear full protective clothing and self-contained breathing apparatus. Hazchem code •3YE.

### SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the surrounding area. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

Page **3** of **7** ISSUE: 5 ISSUE DATE: 22/12/2021

#### **Environmental precautions**

Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Ventilate contaminated area thoroughly.

### Methods and materials for containment and cleaning up

For small spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

### SECTION 7 HANDLING AND STORAGE

#### Precautions for safe handling

Highly flammable product. Avoid breathing vapours. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment.

#### Conditions for safe storage, including any incompatibilities

Bulk storage tanks should be bunded. Store in a well-ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near strong oxidants.

#### SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **Exposure control measures**

From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia -

n-Hexane: 72mg/m³ (20ppm) TWA (8hr) Hydrocarbon: 450mg/m³ TWA (8hr)

Toluene: 191mg/m³ (50ppm) TWA (8hr), 574mg/m³ (150ppm) STEL

### **Biological monitoring**

No biological limit allocated.

#### **Engineering controls**

Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.

#### Individual protection measures

riadai protoction mododico	
Eye and face protection:	Wear safety goggles.
Skin protection:  Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for incidental splashes.	
Respiratory protection:	If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point > 65°C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.
Thermal hazards:	Not applicable.

Page **4** of **7** ISSUE: 5 ISSUE DATE: 22/12/2021

### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colourless liquid
Odour:	Aromatic
Odour threshold (ppm):	Data not available
pH:	Data not available
Melting point/freezing point (°C):	Data not available
Initial boiling point and boiling range (°C):	50 - 135
Flash point (°C):	-30 (Abel)
Evaporation rate (Butyl acetate = 1):	Data not available
Flammability:	Highly flammable
Upper/lower flammability or explosive limits (%):	1.0 – 8.0
Vapour pressure (kPa):	Data not available
Vapour density (air = 1):	> 1
Density (g/ml @ 15°C):	0.77 - 0.81
Solubility (kg/m³):	Negligible
Partition coefficient: n-octanol/water:	Data not available
Auto-ignition temperature (°C):	280
Decomposition temperature (°C):	Data not available
Kinematic viscosity (mm²/s @ 20°C):	Data not available

### SECTION 10 STABILITY AND REACTIVITY

### Reactivity

Stable under normal conditions of use.

### **Chemical stability**

Stable under normal conditions of use.

#### Possibility of hazardous reactions

Stable under normal conditions of use.

### **Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

#### Incompatible materials

Halogens, strong acids and strong oxidising agents.

### **Hazardous decomposition products**

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids, gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

Page **5** of **7** ISSUE DATE: 22/12/2021

#### **SECTION 11 TOXICOLOGICAL INFORMATION**

	Expected to be of low toxicity -	
Acute toxicity:	LD50 Oral (rat) > 2000mg/kg	
Skin corrosion/irritation:	May cause irritation to skin. Prolonged contact may cause defatting of skin which can lead to dermatitis.	
Serious eye damage/irritation:	May cause irritation to eyes.	
Respiratory or skin sensitisation:	Not expected to be a sensitiser.	
Germ cell mutagenicity:	May cause mutagenicity.	
Carcinogenicity:	May be carcinogenic.	
Reproductive toxicity:	Toluene - Experiments have shown reproductive toxicity effects in male and female laboratory animals. Suspected human reproductive toxicant. Damage to foetus possible	
Specific Target Organ Toxicity (STOT) – single exposure:	Expected to be of low toxicity: LC50 > 20 mg/l (4 hours, rat).  May cause irritation to the respiratory system.	
Specific Target Organ Toxicity (STOT) – repeated exposure:	Central nervous system: repeated exposure affects the nervous system.  Effects seen at high doses only. Continued inhalation may result in unconsciousness and/or death.  Respiratory system: repeated exposure affects the respiratory system.  Effects seen at high doses only.  Auditory system: prolonged and repeated exposure to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss	
Aspiration hazard:	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.	

#### SECTION 12 **ECOLOGICAL INFORMATION**

### **Ecotoxicity**

Acute toxicity:

Fish –	Expected to be toxic: 1 < LC/EC/IC50 <= 10mg/l
Aquatic invertebrate –	Expected to be toxic: 1 < LC/EC/IC50 <= 10mg/l
Algae –	Expected to be toxic: 1 < LC/EC/IC50 <= 10mg/l
Microorganisms –	Expected to have low toxicity: LC/EC/IC50 > 100mg/l

### Chronic toxicity:

Fish –	Data not available
Aquatic invertebrate –	Data not available
Algae –	Data not available
Microorganisms –	Data not available

Persistence and degradability
Readily biodegradable. Oxidises by photo-chemical reactions in air.

### **Bioaccumulative potential**

Has the potential to bioaccumulate.

Page **6** of **7** ISSUE: 5 ISSUE DATE: 22/12/2021

#### Mobility in soil

Floats on water. Adsorbs to soil and has low mobility.

### Other adverse effects

Data not available.

### SECTION 13 DISPOSAL CONSIDERATIONS

Ensure waste disposal conforms to local waste disposal regulations.

### **SECTION 14 TRANSPORT INFORMATION**

UN number:	1993
Proper shipping name:	Flammable Liquid N.O.S.
Australian Dangerous Goods class:	3
Australian Dangerous Goods packing group:	II
Hazchem code:	●3YE

### **SECTION 15 REGULATORY INFORMATION**

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:	6
Australian Inventory of Chemical Substances (AICS):	Listed
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76):	14
New Zealand HSNO, Classification:	Solvents (Flammable) Group Standard Classification - 3.1C, 6.1E, 6.3B, 9.1B

#### **SECTION 16 OTHER INFORMATION**

Date of preparation:	22/12/2021
Revision number:	5
Changes in this revision:	Reviewed due to expiration

This SDS summarises product safety information at the date of issue, to the best of our knowledge, as a general guide. Recochem cannot anticipate or control the conditions under which the product is used, so prior to usage each user must assess and control the risks associated with their use of the product. Users should also consult the relevant legislation governing the use and storage of this product. We make no warranties, express or implied, and assume no liability in connection with any use of information contained within this document. If clarification or further information is needed, the user should contact Recochem on (07) 3308 5200.

Page **7** of **7** ISSUE DATE: 22/12/2021